



◆ 产品特点

- 广泛应用于数控机床
- 2路正交输出信号 (A,B)
- 分辨率25、100脉冲
- 长线驱动、电压输出等输出方式可选

◆ Features

- Widely used with CNC machine tools
- 2 quadrature output channel (A&B)
- Resolution 25, 100 cpr
- Output Form: Line Driver, TTL on option

◆ 型号说明 Ordering Information

RGT600	-	001	-	100		B	-	5		L
				分辨率 Resolution					工作电压 Supply Voltage	输出方式/ Output Mode
				100: 100 cpr					5: 5V DC	E: 电压输出/TTL
				25: 25 cpr					12: 12V DC	L: 长线驱动/Line Driver
									5-12: 7~12V DC	F: 推拉输出/ Push-Pull
										C: 集电极开路NPN Open Collector NPN

备注 / Note:

- 1 下单前请联系销售人员确认型号
Please contact sales representative to confirm the correctness and availability of the part number
- 2 长线驱动仅5V可选
Line driver only available with 5V DC


◆ 技术参数 Technical Specifications

参数/Parameter	标准数值/Typ Value	备注/Note
电源电压/supply Voltage	DC 5V / 12V / 5~12V ($\pm 10\%$)	*1 最大响应频率受限于最大转速
最大响应频率/Max. Response Frequency	20 kHz	Max. response frequency is gated by max. rotation speed
最大转速/Max. Rotation Speed (*1)	200 rpm	
最大消耗电流/Max. Current Consumption	120mA (空载/Unloaded 长线驱动/Line Driver)	
最大消耗电流/Max. Current Consumption	100mA (空载/Unloaded 其他输出/Other Output)	
最大上升-下降时间/Max. Rise-Fall Time	20us	
最大工作温度/Max. Operating Temperature	-10 ~ 70°C	
储存温度/Storage Temperature	-10 ~ 70°C	
湿度/Humidity	30%~85% 无结露 / no condensation	
振动/Vibration	5G	
防护等级/IP Rating	设计防护等级IP40 by design	

◆ 接线表 Connection Table

输出信号 Output Signal	A+	B+	0V	Vcc	A-	B-
端子代号-长线驱动 Terminal - Line Driver	1	2	3	4	5	6
端子代号-其他输出 Terminal - Other Output	1	2	3	4	n/a	n/a

◆ 输出波形 Output Waveform



◆ 产品尺寸 Dimensions

