

TYB 系列三相永磁同步电动机主要技术数据

型号	功率范围 (kW)	电压范围 (V)	额定电流 (A)	调频范围 (Hz)	调速范围 (r/min)	额定转矩 (N.m)	机座号
TYBX30-42-82	0.03-0.3-0.5	23-230-380	1.8	5-50-82	150-1500-2460	1.91	801
TYB75-42-80	0.15-0.75-1.2	48-238-380	3.2	10-50-80	300-1500-2400	4.78	802
TYB110-4	0.22-1.1	76-380	2.8	10-50	300-1500	7	90S
TYB150-4	0.3-1.5	76-380	3.4	10-50	300-1500	9.55	90L
TYBZ150-4	0.19-0.94-1.5	48-238-380	3.4	10-50-80	300-1500-2400	5.97	90L
TYB138-42-80	0.17-1.38-2.2	29-238-380	4.5	6-50-80	180-1500-2400	8.75	100L2
TYB220-4	0.44-2.2	76-380	5	10-50	300-1500	14	100L1
TYBZ220-4	0.28-1.38-2.2	48-238-380	5.2	10-50-80	300-1500-2400	8.75	100L1
TYB300-4	0.6-3	76-380	6.2	10-50	300-1500	19.1	100L2
TYBZ300-4	0.38-1.88-3	48-238-380	6.2	10-50-80	300-1500-2400	11.94	100L2
TYB325-42-80	0.39-3.25-5.22	39-238-380	10	6-50-80	180-1500-2400	20.69	112M
TYB400-4	0.8-4	76-380	9	10-50	300-1500	25.47	112M
TYB550-4	1.1-5.5	76-380	11	10-50	300-1500	35	132S
TYB750-4	15-7.5	76-380	15	10-50	300-1500	48	132M

TYB1100-4	2.2-11	76-380	23	10-50	300-1500	70	160L
TYB1500-4	3-15	76-380	27	10-50	300-1500	95.5	160L
TYBX60-65-100	0.06-0.6-1.2	19-140-280	4.5	5-50-100	100-1000-2000	5.73	90S
TYBZ80-6	0.06-0.75-1.1	20-253-380	3.4	4-50-75	80-1000-1500	7	90S
TYBX52-67-126	0.26-0.52-1.31	75-150-378	4.5	25-50-126	500-1000-2520	4.97	90L
TYB75-6	0.38-0.75-2.25	63-125-375	5.6	20-50-150	500-1000-3000	7.13	112M
TYB220-6	0.73-1.83-2.2	126-317-380	4.9	20-50-60	400-1000-1200	17.5	112M
TYB300-6	0.6-3	76-380	6	10-50	200-1000	28.65	112M
TYB220-8	0.44-2.22	76-380	5	10-50	150-750	28.01	112M
TYBX400-8-50	0.27-4	26-380	10	3.33-50	50-750	50.93	180M
TYB630-8	3.15-6.3-12.6	95-190-380	28	25-50-100	375-750-1500	80	180L
TYB750-8	1.2-7.5-15	30-190-380	30	8-50-100	120-750-1500	96	180L
TYB900-8	1.13-9-18	24-190-380	35	6.25-50-100	94-750-1500	110	180L
TYB1100-8	1.37-11-22	24-190-380	45	6.25-50-100	94-750-1500	140.2	225M
TYB1500-8	1.88-15-30	24-190-380	55	6.25-50-100	94-750-1500	191	225M