

安装方式			埋入式	非埋入式
检测距离			12mm	18mm
交流AC90-250V	二线制	NO 常开	FA38-M12KA	FA38-18KA
		NC 常闭	FA38-M12KB	FA38-18KB
	三线制	NO+NC 常开常闭	FA38-M12KE	FA38-18KE
继电输出四线		NO+NC 常开常闭	FA38-M12KC	FA38-18KC
继电输出五线		NO+NC 常开常闭	FA38-M12JC	FA38-18JC
直流DC6-36V	NPN	NO 常开	FA38-M12NA	FA38-18NA
		NC 常闭	FA38-M12NB	FA38-18NB
		NO+NC 常开常闭	FA38-M12NC	FA38-18NC
	PNP	NO 常开	FA38-M12PA	FA38-18PA
		NC 常闭	FA38-M12PB	FA38-18PB
		NO+NC 常开常闭	FA38-M12PC	FA38-18PC
	二线制	NO 常开	FA38-M12LA	FA38-18LA
		NC 常闭	FA38-M12LB	FA38-18LB
输出电压降DC/AC			AC<8V DC三线<1.5V,DC二线<4V	
输出电流			可控硅SCR 300mA 继电器1A、2A DC三线200mA DC二线 50mA	
重复精度			≤10%	
消耗电流			<10mA	
响应频率			DC 200Hz,AC 25Hz	DC 100Hz,AC 25Hz
外壳体材料			金属/塑料ABS	
设定距离			0-9.6mm	0-14.4mm
标准检测物体			40×40×1	
工作环境温度			-20℃~+55℃	
连接方式			1.5m PVC电缆	
防护等级			IP67	