

安装方式			埋入式	非埋入式
检测距离			10mm	15mm
交流AC90-250V	二线制	NO 常开	FJ2-M10KA	FJ2-15KA
		NC 常闭	FJ2-M10KB	FJ2-15KB
	三线制	NO+NC 常开常闭	FJ2-M10KE	FJ2-15KE
继电器输出四线		NO+NC 常开常闭	FJ2-M10KC	FJ2-15KC
继电器输出五线		NO+NC 常开常闭	FJ2-M10JC	FJ2-15JC
直流DC6-36V	NPN	NO 常开	FJ2-M10NA	FJ2-15NA
		NC 常闭	FJ2-M10NB	FJ2-15NB
		NO+NC 常开常闭	FJ2-M10NC	FJ2-15NC
	PNP	NO 常开	FJ2-M10PA	FJ2-15PA
		NC 常闭	FJ2-M10PB	FJ2-15PB
		NO+NC 常开常闭	FJ2-M10PC	FJ2-15PC
	二线制	NO 常开	FJ2-M10LA	FJ2-15LA
		NC 常闭	FJ2-M10LB	FJ2-15LB
输出电压降DC/AC			AC<8V ,DC三线<1.5V ,DC二线<4V	
输出电流			可控硅SCR 300mA 继电器1A、 2A DC三线200mA DC二线 50mA	
重复精度			≤10%	
消耗电流			<10mA	
响应频率			DC 200Hz,AC 25Hz	DC 100Hz,AC 25Hz
外壳体材料			塑料ABS	
设定距离			0-8mm	0-12mm
标准检测物体			50×50×1	
工作环境温度			-20℃~+55℃	
连接方式			1.5m PVC电缆	
防护等级			IP67	