

安装方式			埋入式	非埋入式
检测距离				20mm
交流AC90-250V	二线制	NO 常开		FJ10-20KA
		NC 常闭		FJ10-20KB
	三线制	NO+NC 常开常闭		FJ10-20KE
继电输出四线		NO+NC 常开常闭		FJ10-20KC
继电输出五线		NO+NC 常开常闭		FJ10-20JC
直流DC6-36V	NPN	NO 常开		FJ10-20NA
		NC 常闭		FJ10-20NB
		NO+NC 常开常闭		FJ10-20NC
	PNP	NO 常开		FJ10-20PA
		NC 常闭		FJ10-20PB
		NO+NC 常开常闭		FJ10-20PC
	二线制	NO 常开		FJ10-20LA
		NC 常闭		FJ10-20LB
输出电压降DC/AC			AC<8V ,DC三线<1.5V ,DC二线<4V	
输出电流			可控硅SCR 300mA 继电器1A、2A DC三线200mA DC二线 50mA	
重复精度			≤10%	
消耗电流			<10mA	
响应频率			DC 200Hz,AC 10Hz	
外壳体材料			塑料ABS	
设定距离			0-16mm	
标准检测物体			45×45×1 (铁)	
工作环境温度			-20℃~+55℃	
连接方式			1.5m PVC电缆	
防护等级			IP67	