

安装方式			埋入式	非埋入式
检测距离			2mm	4mm
交流AC90-250V	二线制	NO 常开	FJ11-M2KA	FJ11-4KA
		NC 常闭	FJ11-M2KB	FJ11-4KB
	三线制	NO+NC 常开常闭		
继电输出四线		NO+NC 常开常闭		
继电输出五线		NO+NC 常开常闭		
直流DC6-36V	NPN	NO 常开	FJ11-M2NA	FJ11-4NA
		NC 常闭	FJ11-M2NB	FJ11-4NB
		NO+NC 常开常闭	FJ11-M2NC	FJ11-4NC
	PNP	NO 常开	FJ11-M2PA	FJ11-4PA
		NC 常闭	FJ11-M2PB	FJ11-4PB
		NO+NC 常开常闭	FJ11-M2PC	FJ11-4PC
	二线制	NO 常开	FJ11-M2LA	FJ11-4LA
		NC 常闭	FJ11-M2LB	FJ11-4LB
输出电压降DC/AC			AC<8V ,DC三线<1.5V ,DC二线<4V	
输出电流			可控硅SCR 300mA 继电器1A、2A DC三线200mA DC二线 50mA	
重复精度			≤10%	
消耗电流			<10mA	
响应频率			DC 800Hz,AC 25Hz	DC 400Hz,AC 25Hz
外壳体材料			塑料ABS	
设定距离			0-1.6	0-3.2mm
标准检测物体			15×15×1 (铁)	
工作环境温度			-20℃~+55℃	
连接方式			1.5m PVC电缆	
防护等级			IP67	