

安装方式			埋入式	非埋入式
检测距离				12mm
交流AC90-250V	二线制	NO 常开		FJ21-12KA
		NC 常闭		FJ21-12KB
	三线制	NO+NC 常开常闭		FJ21-12KE
继电器输出四线		NO+NC 常开常闭		FJ21-12JT (JWK220-A10J)
继电器输出五线		NO+NC 常开常闭		FJ21-12JC (JWK220-A10JK)
直流DC6-36V	NPN	NO 常开		FJ21-12NA
		NC 常闭		FJ21-12NB
		NO+NC 常开常闭		FJ21-12NC
	PNP	NO 常开		FJ21-12PA
		NC 常闭		FJ21-12PB
		NO+NC 常开常闭		FJ21-12PC
	二线制	NO 常开		FJ21-12LA
		NC 常闭		FJ21-12LB
输出电压降DC/AC			AC<8V ,DC三线<1.5V ,DC二线<4V	
输出电流			可控硅SCR 300mA 继电器1A、2A DC三线200mA DC二线 50mA	
重复精度			≤10%	
消耗电流			<10mA	
响应频率			DC 40Hz,AC 10Hz	
外壳体材料			塑料ABS	
设定距离			0-9.6mm	
标准检测物体			45×45×1 (铁)	
工作环境温度			-20℃~+55℃	
连接方式			1.5m PVC电缆	
防护等级			IP67	