

公称力 capacity	1000 (kN)	公称力行程 Nominal force stroke	10 (mm)
滑块行程 Length or slide stroke	140 (mm)	滑块行程次数 strokes per minutes	45 (spm)
最大装模高度 Max shut height	290 (mm)	装模高度调节量 Adjust of shut height	110 (mm)
喉深 Depth of throat	900 (mm)	工作台尺寸 (左右×前后) Table area (LR×FB)	1080×710 (mm)
滑块底面尺寸 (左右×前后) Slide area (LR×FB)	490×400 (mm)	立柱间距离 Distance between uprights	560 (mm)
模柄孔尺寸 (直径×深度) Shank hole (dia/deep)	Φ60×80 (mm)	工作台板厚度 Bolster thickness	110 (mm)
工作台离地面高度 Bolster surface height from floor	1010 (mm)	外形尺寸 (左右×前后×高) Overall dimensions (L×W×H)	1644×2820×3080 (mm)
电动机功率 Main motor	7.5 (kW)	重量 Weight	11000 (kg)

公称力 capacity	800 (kN)	公称力行程 Nominal force stroke	9 (mm)
滑块行程 Length or slide stroke	130 (mm)	滑块行程次数 strokes per minutes	45 (spm)
最大装模高度 Max shut height	280 (mm)	装模高度调节量 Adjust of shut height	100 (mm)
喉深 Depth of throat	800 (mm)	工作台尺寸 (左右×前后) Table area (LR×FB)	920×570 (mm)
滑块底面尺寸 (左右×前后) Slide area (LR×FB)	420×375 (mm)	立柱间距离 Distance between uprights	480 (mm)
模柄孔尺寸 (直径×深度) Shank hole (dia/deep)	Φ60×80 (mm)	工作台板厚度 Bolster thickness	100 (mm)
工作台离地面高度 Bolster surface height from floor	950 (mm)	外形尺寸 (左右×前后×高) Overall dimensions (L×W×H)	1554×2528×2880 (mm)
电动机功率 Main motor	5.5 (kW)	重量 Weight	8800 (kg)

公称力 capacity	630 (kN)	公称力行程 Nominal force stroke	7 (mm)
滑块行程 Length or slide stroke	100 (mm)	滑块行程次数 strokes per minutes	40 (spm)
最大装模高度 Max shut height	320 (mm)	装模高度调节量 Adjust of shut height	80 (mm)
喉深 Depth of throat	700 (mm)	工作台尺寸 (左右×前后) Table area (LR×FB)	860×570 (mm)
滑块底面尺寸 (左右×前后) Slide area (LR×FB)	400×360 (mm)	立柱间距离 Distance between uprights	530 (mm)
模柄孔尺寸 (直径×深度) Shank hole (dia/deep)	Φ50×70 (mm)	工作台板厚度 Bolster thickness	80 (mm)
工作台离地面高度 Bolster surface height from floor	930 (mm)	外形尺寸 (左右×前后×高) Overall dimensions (L×W×H)	1482×2340×2868 (mm)
电动机功率 Main motor	5.5 (kW)	重量 Weight	7400 (kg)

公称力 capacity	400 (kN)	公称力行程 Nominal force stroke	6 (mm)
滑块行程 Length or slide stroke	80 (mm)	滑块行程次数 strokes per minutes	45 (spm)
最大装模高度 Max shut height	285 (mm)	装模高度调节量 Adjust of shut height	65 (mm)
喉深 Depth of throat	600 (mm)	工作台尺寸 (左右×前后) Table area (LR×FB)	700×460 (mm)
滑块底面尺寸 (左右×前后) Slide area (LR×FB)	300×260 (mm)	立柱间距离 Distance between uprights	430 (mm)
模柄孔尺寸 (直径×深度) Shank hole (dia/deep)	φ50×70 (mm)	工作台板厚度 Bolster thickness	65 (mm)
工作台离地面高度 Bolster surface height from floor	915 (mm)	外形尺寸 (左右×前后×高) Overall dimensions (L×W×H)	1319×2025×2490 (mm)
电动机功率 Main motor	4 (kW)	重量 Weight	5000 (kg)

