

公称力 Nominal capacity	400 (kN)	公称力行程 Rated tonnage point	2.8 (mm)
滑块行程 Length of stroke	80 (mm)	行程次数 Strokes per minute	45 (mm)
最大装模高度 Max. die height	255 (mm)	装模高度调节量 Slide adjustment	65 (mm)
喉深 Depth of throat	250 (mm)	工作台尺寸 (前后×左右) Bolster area (FB×LR)	460×720 (mm)
滑块底面尺寸 (前后×左右) Slide area (FB×LR)	260×300 (mm)	模柄孔尺寸 (直径/深度) Shank hole (Dia/Depth)	Φ50/70 (mm)
工作台板厚度 Bolster thickness	75 (mm)	电机功率 Power of motor	4 (kW)
外形尺寸 (左右) Overall Dimensions (LR)	1235 (mm)	外形尺寸 (前后) Overall Dimensions (FB)	1724 (mm)
外形尺寸 (高度) Overall dimensions (H)	2438 (mm)	机器重量 Net Weight (about)	3800 (kg)
工作台面离地高度 Bolster surface height from floor	875 (mm)		

公称力 Nominal capacity	630 (kN)	公称力行程 Rated tonnage point	4 (mm)
滑块行程 Length of stroke	120 (mm)	行程次数 Strokes per minute	40 (mm)
最大装模高度 Max. die height	270 (mm)	装模高度调节量 Slide adjustment	80 (mm)
喉深 Depth of throat	290 (mm)	工作台尺寸 (前后×左右) Bolster area (FB×LR)	540×840 (mm)
滑块底面尺寸 (前后×左右) Slide area (FB×LR)	290×330 (mm)	模柄孔尺寸 (直径/深度) Shank hole (Dia/Depth)	Φ50/70 (mm)
工作台板厚度 Bolster thickness	80 (mm)	电机功率 Power of motor	5.5 (kW)
外形尺寸 (左右) Overall Dimensions (LR)	1445 (mm)	外形尺寸 (前后) Overall Dimensions (FB)	1896 (mm)
外形尺寸 (高度) Overall dimensions (H)	2810 (mm)	机器重量 Net Weight (about)	5800 (kg)
工作台面离地高度 Bolster surface height from floor	880 (mm)		

公称力 Nominal capacity	800 (kN)	公称力行程 Rated tonnage point	4 (mm)
滑块行程 Length of stroke	120 (mm)	行程次数 Strokes per minute	40 (mm)
最大装模高度 Max. die height	295 (mm)	装模高度调节量 Slide adjustment	80 (mm)
喉深 Depth of throat	310 (mm)	工作台尺寸 (前后×左右) Bolster area (FB×LR)	570×920 (mm)
滑块底面尺寸 (前后×左右) Slide area (FB×LR)	340×400 (mm)	模柄孔尺寸 (直径/深度) Shank hole (Dia/Depth)	Φ60/70 (mm)
工作台板厚度 Bolster thickness	95 (mm)	电机功率 Power of motor	5.5 (kW)
外形尺寸 (左右) Overall Dimensions (LR)	1500 (mm)	外形尺寸 (前后) Overall Dimensions (FB)	1895 (mm)
外形尺寸 (高度) Overall dimensions (H)	2915 (mm)	机器重量 Net Weight (about)	6500 (kg)
工作台面离地高度 Bolster surface height from floor	895 (mm)		

公称力 Nominal capacity	1000 (kN)	公称力行程 Rated tonnage point	5 (mm)
滑块行程 Length of stroke	130 (mm)	行程次数 Strokes per minute	38 (mm)
最大装模高度 Max. die height	365 (mm)	装模高度调节量 Slide adjustment	100 (mm)
喉深 Depth of throat	380 (mm)	工作台尺寸 (前后×左右) Bolster area (FB×LR)	710×1080 (mm)
滑块底面尺寸 (前后×左右) Slide area (FB×LR)	360×430 (mm)	模柄孔尺寸 (直径/深度) Shank hole (Dia/Depth)	Φ60/85 (mm)
工作台板厚度 Bolster thickness	115 (mm)	电机功率 Power of motor	7.5 (kW)
外形尺寸 (左右) Overall Dimensions (LR)	1723 (mm)	外形尺寸 (前后) Overall Dimensions (FB)	2353 (mm)
外形尺寸 (高度) Overall dimensions (H)	3310 (mm)	机器重量 Net Weight (about)	11300 (kg)
工作台面离地高度 Bolster surface height from floor	995 (mm)		

公称力 Nominal capacity	1250 (kN)	公称力行程 Rated tonnage point	5 (mm)
滑块行程 Length of stroke	140 (mm)	行程次数 Strokes per minute	38 (mm)
最大装模高度 Max. die height	380 (mm)	装模高度调节量 Slide adjustment	100 (mm)
喉深 Depth of throat	380 (mm)	工作台尺寸 (前后×左右) Bolster area (FB×LR)	710×1100 (mm)
滑块底面尺寸 (前后×左右) Slide area (FB×LR)	360×430 (mm)	模柄孔尺寸 (直径/深度) Shank hole (Dia/Depth)	Φ60/85 (mm)
工作台板厚度 Bolster thickness	115 (mm)	电机功率 Power of motor	7.5 (kW)
外形尺寸 (左右) Overall Dimensions (LR)	1723 (mm)	外形尺寸 (前后) Overall Dimensions (FB)	2353 (mm)
外形尺寸 (高度) Overall dimensions (H)	3310 (mm)	机器重量 Net Weight (about)	11800 (kg)
工作台面离地高度 Bolster surface height from floor	995 (mm)		

公称力 Nominal capacity	1600 (kN)	公称力行程 Rated tonnage point	8 (mm)
滑块行程 Length of stroke	140 (mm)	行程次数 Strokes per minute	38 (mm)
最大装模高度 Max. die height	335 (mm)	装模高度调节量 Slide adjustment	100 (mm)
喉深 Depth of throat	380 (mm)	工作台尺寸 (前后×左右) Bolster area (FB×LR)	710×1160 (mm)
滑块底面尺寸 (前后×左右) Slide area (FB×LR)	360×430 (mm)	模柄孔尺寸 (直径/深度) Shank hole (Dia/Depth)	Φ60/90 (mm)
工作台板厚度 Bolster thickness	140 (mm)	电机功率 Power of motor	11 (kW)
外形尺寸 (左右) Overall Dimensions (LR)	1853 (mm)	外形尺寸 (前后) Overall Dimensions (FB)	2490 (mm)
外形尺寸 (高度) Overall dimensions (H)	3330 (mm)	机器重量 Net Weight (about)	13500 (kg)
工作台面离地高度 Bolster surface height from floor	980 (mm)		

公称力 Nominal capacity	2000 (kN)	公称力行程 Rated tonnage point	6 (mm)
滑块行程 Length of stroke	145 (mm)	行程次数 Strokes per minute	38 (mm)
最大装模高度 Max. die height	357 (mm)	装模高度调节量 Slide adjustment	100 (mm)
喉深 Depth of throat	400 (mm)	工作台尺寸 (前后×左右) Bolster area (FB×LR)	750×1200 (mm)
滑块底面尺寸 (前后×左右) Slide area (FB×LR)	380×500 (mm)	模柄孔尺寸 (直径/深度) Shank hole (Dia/Depth)	Φ60/90 (mm)
工作台板厚度 Bolster thickness	140 (mm)	电机功率 Power of motor	11 (kW)
外形尺寸 (左右) Overall Dimensions (LR)	1963 (mm)	外形尺寸 (前后) Overall Dimensions (FB)	2593 (mm)
外形尺寸 (高度) Overall dimensions (H)	3435 (mm)	机器重量 Net Weight (about)	16800 (kg)
工作台面离地高度 Bolster surface height from floor	950 (mm)		

公称力 Nominal capacity	3000 (kN)	公称力行程 Rated tonnage point	6 (mm)
滑块行程 Length of stroke	150 (mm)	行程次数 Strokes per minute	32 (mm)
最大装模高度 Max. die height	420 (mm)	装模高度调节量 Slide adjustment	100 (mm)
喉深 Depth of throat	400 (mm)	工作台尺寸 (前后×左右) Bolster area (FB×LR)	770×1400 (mm)
滑块底面尺寸 (前后×左右) Slide area (FB×LR)	450×600 (mm)	模柄孔尺寸 (直径/深度) Shank hole (Dia/Depth)	Φ60/90 (mm)
工作台板厚度 Bolster thickness	160 (mm)	电机功率 Power of motor	22 (kW)
外形尺寸 (左右) Overall Dimensions (LR)	2295 (mm)	外形尺寸 (前后) Overall Dimensions (FB)	2942 (mm)
外形尺寸 (高度) Overall dimensions (H)	3670 (mm)	机器重量 Net Weight (about)	22000 (kg)
工作台面离地高度 Bolster surface height from floor	970 (mm)		