

|                                               |              |                                         |              |
|-----------------------------------------------|--------------|-----------------------------------------|--------------|
| 公称力<br>Nominal capacity                       | 400 (kN)     | 公称力行程<br>Rated tonnage point            | 2.8 (mm)     |
| 滑块行程<br>Length of stroke                      | 80 (mm)      | 行程次数<br>Strokes per minute              | 45 (mm)      |
| 最大装模高度<br>Max. die height                     | 255 (mm)     | 装模高度调节量<br>Slide adjustment             | 85 (mm)      |
| 喉深<br>Depth of throat                         | 250 (mm)     | 工作台尺寸 (前后×左右)<br>Bolster area (FB×LR)   | 460×720 (mm) |
| 滑块底面尺寸 (前后×左右)<br>Slide area (FB×LR)          | 260×300 (mm) | 模柄孔尺寸 (直径/深度)<br>Shank hole (Dia/Depth) | φ50/70 (mm)  |
| 工作台板厚度<br>Bolster thickness                   | 75 (mm)      | 电机功率<br>Power of motor                  | 4 (kW)       |
| 外形尺寸 (左右)<br>Overall Dimensions (LR)          | 1235 (mm)    | 外形尺寸 (前后)<br>Overall Dimensions (FB)    | 1724 (mm)    |
| 外形尺寸 (高度)<br>Overall dimensions (H)           | 2438 (mm)    | 机器重量<br>Net Weight (about)              | 3800 (kg)    |
| 工作台面离地高度<br>Bolster surface height from floor | 875 (mm)     |                                         |              |

|                                               |              |                                         |              |
|-----------------------------------------------|--------------|-----------------------------------------|--------------|
| 公称力<br>Nominal capacity                       | 630 (kN)     | 公称力行程<br>Rated tonnage point            | 4 (mm)       |
| 滑块行程<br>Length of stroke                      | 120 (mm)     | 行程次数<br>Strokes per minute              | 40 (mm)      |
| 最大装模高度<br>Max. die height                     | 270 (mm)     | 装模高度调节量<br>Slide adjustment             | 80 (mm)      |
| 喉深<br>Depth of throat                         | 290 (mm)     | 工作台尺寸 (前后×左右)<br>Bolster area (FB×LR)   | 540×840 (mm) |
| 滑块底面尺寸 (前后×左右)<br>Slide area (FB×LR)          | 290×330 (mm) | 模柄孔尺寸 (直径/深度)<br>Shank hole (Dia/Depth) | φ50/70 (mm)  |
| 工作台板厚度<br>Bolster thickness                   | 80 (mm)      | 电机功率<br>Power of motor                  | 5.5 (kW)     |
| 外形尺寸 (左右)<br>Overall Dimensions (LR)          | 1445 (mm)    | 外形尺寸 (前后)<br>Overall Dimensions (FB)    | 1896 (mm)    |
| 外形尺寸 (高度)<br>Overall dimensions (H)           | 2810 (mm)    | 机器重量<br>Net Weight (about)              | 5600 (kg)    |
| 工作台面离地高度<br>Bolster surface height from floor | 880 (mm)     |                                         |              |

|                                               |              |                                       |               |
|-----------------------------------------------|--------------|---------------------------------------|---------------|
| 公称力<br>Nominal capacity                       | 800 (kN)     | 公称力行程<br>Rated tonnage point          | 4 (mm)        |
| 滑块行程<br>Length of stroke                      | 120 (mm)     | 行程次数<br>Strokes per minute            | 40 (mm)       |
| 最大装模高度<br>Max. die height                     | 295 (mm)     | 装模高度调节量<br>Slide adjustment           | 80 (mm)       |
| 喉深<br>Depth of throat                         | 310 (mm)     | 工作台尺寸 (前后×左右)<br>Bolster area (FB×LR) | 570×920 (mm)  |
| 滑块底面尺寸 (前后×左右)<br>Slide area (FB×LR)          | 340×400 (mm) | 模柄孔尺寸 (直径/深度)<br>Shank hole Dia/Depth | Φ60/70 (mm)   |
| 工作台板厚度<br>Bolster thickness                   | 95 (mm)      | 电机功率<br>Power of motor                | 5.5 (kW)      |
| 外形尺寸 (左右)<br>Overall Dimensions (LR)          | 1500 (mm)    | 外形尺寸 (前后)<br>Overall Dimensions (FB)  | 1895 (mm)     |
| 外形尺寸 (高度)<br>Overall dimensions (H)           | 2915 (mm)    | 机器重量<br>Net Weight (about)            | 6500 (kg)     |
| 工作台面离地高度<br>Bolster surface height from floor | 895 (mm)     |                                       |               |
| 公称力<br>Nominal capacity                       | 1000 (kN)    | 公称力行程<br>Rated tonnage point          | 5 (mm)        |
| 滑块行程<br>Length of stroke                      | 130 (mm)     | 行程次数<br>Strokes per minute            | 38 (mm)       |
| 最大装模高度<br>Max. die height                     | 365 (mm)     | 装模高度调节量<br>Slide adjustment           | 100 (mm)      |
| 喉深<br>Depth of throat                         | 380 (mm)     | 工作台尺寸 (前后×左右)<br>Bolster area (FB×LR) | 710×1080 (mm) |
| 滑块底面尺寸 (前后×左右)<br>Slide area (FB×LR)          | 360×430 (mm) | 模柄孔尺寸 (直径/深度)<br>Shank hole Dia/Depth | Φ60/85 (mm)   |
| 工作台板厚度<br>Bolster thickness                   | 115 (mm)     | 电机功率<br>Power of motor                | 7.5 (kW)      |
| 外形尺寸 (左右)<br>Overall Dimensions (LR)          | 1723 (mm)    | 外形尺寸 (前后)<br>Overall Dimensions (FB)  | 2353 (mm)     |
| 外形尺寸 (高度)<br>Overall dimensions (H)           | 3310 (mm)    | 机器重量<br>Net Weight (about)            | 11300 (kg)    |
| 工作台面离地高度<br>Bolster surface height from floor | 995 (mm)     |                                       |               |

|                                               |              |                                         |               |
|-----------------------------------------------|--------------|-----------------------------------------|---------------|
| 公称力<br>Nominal capacity                       | 1250 (kN)    | 公称力行程<br>Rated tonnage point            | 5 (mm)        |
| 滑块行程<br>Length of stroke                      | 140 (mm)     | 行程次数<br>Strokes per minute              | 38 (mm)       |
| 最大装模高度<br>Max. die height                     | 360 (mm)     | 装模高度调节量<br>Slide adjustment             | 100 (mm)      |
| 喉深<br>Depth of throat                         | 380 (mm)     | 工作台尺寸 (前后×左右)<br>Bolster area (FB×LR)   | 710×1100 (mm) |
| 滑块底面尺寸 (前后×左右)<br>Slide area (FB×LR)          | 360×430 (mm) | 模柄孔尺寸 (直径/深度)<br>Shank hole (Dia/Depth) | Φ60/85 (mm)   |
| 工作台板厚度<br>Bolster thickness                   | 115 (mm)     | 电机功率<br>Power of motor                  | 7.5 (kW)      |
| 外形尺寸 (左右)<br>Overall Dimensions (LR)          | 1723 (mm)    | 外形尺寸 (前后)<br>Overall Dimensions (FB)    | 2353 (mm)     |
| 外形尺寸 (高度)<br>Overall dimensions (H)           | 3310 (mm)    | 机器重量<br>Net Weight (about)              | 11800 (kg)    |
| 工作台面离地高度<br>Bolster surface height from floor | 995 (mm)     |                                         |               |

|                                               |              |                                         |               |
|-----------------------------------------------|--------------|-----------------------------------------|---------------|
| 公称力<br>Nominal capacity                       | 1600 (kN)    | 公称力行程<br>Rated tonnage point            | 8 (mm)        |
| 滑块行程<br>Length of stroke                      | 140 (mm)     | 行程次数<br>Strokes per minute              | 38 (mm)       |
| 最大装模高度<br>Max. die height                     | 335 (mm)     | 装模高度调节量<br>Slide adjustment             | 100 (mm)      |
| 喉深<br>Depth of throat                         | 380 (mm)     | 工作台尺寸 (前后×左右)<br>Bolster area (FB×LR)   | 710×1160 (mm) |
| 滑块底面尺寸 (前后×左右)<br>Slide area (FB×LR)          | 360×430 (mm) | 模柄孔尺寸 (直径/深度)<br>Shank hole (Dia/Depth) | Φ60/90 (mm)   |
| 工作台板厚度<br>Bolster thickness                   | 140 (mm)     | 电机功率<br>Power of motor                  | 11 (kW)       |
| 外形尺寸 (左右)<br>Overall Dimensions (LR)          | 1853 (mm)    | 外形尺寸 (前后)<br>Overall Dimensions (FB)    | 2490 (mm)     |
| 外形尺寸 (高度)<br>Overall dimensions (H)           | 3330 (mm)    | 机器重量<br>Net Weight (about)              | 13500 (kg)    |
| 工作台面离地高度<br>Bolster surface height from floor | 980 (mm)     |                                         |               |

|                                               |              |                                         |               |
|-----------------------------------------------|--------------|-----------------------------------------|---------------|
| 公称力<br>Nominal capacity                       | 2000 (kN)    | 公称力行程<br>Rated tonnage point            | 5 (mm)        |
| 滑块行程<br>Length of stroke                      | 145 (mm)     | 行程次数<br>Strokes per minute              | 38 (mm)       |
| 最大装模高度<br>Max. die height                     | 357 (mm)     | 装模高度调节量<br>Slide adjustment             | 100 (mm)      |
| 喉深<br>Depth of throat                         | 400 (mm)     | 工作台尺寸 (前后×左右)<br>Bolster area (FB×LR)   | 750×1200 (mm) |
| 滑块底面尺寸 (前后×左右)<br>Slide area (FB×LR)          | 380×500 (mm) | 模柄孔尺寸 (直径/深度)<br>Shank hole (Dia/Depth) | Φ60/90 (mm)   |
| 工作台板厚度<br>Bolster thickness                   | 140 (mm)     | 电机功率<br>Power of motor                  | 11 (kW)       |
| 外形尺寸 (左右)<br>Overall Dimensions (LR)          | 1963 (mm)    | 外形尺寸 (前后)<br>Overall Dimensions (FB)    | 2593 (mm)     |
| 外形尺寸 (高度)<br>Overall dimensions (H)           | 3435 (mm)    | 机器重量<br>Net Weight (about)              | 16800 (kg)    |
| 工作台面离地高度<br>Bolster surface height from floor | 950 (mm)     |                                         |               |
| 公称力<br>Nominal capacity                       | 3000 (kN)    | 公称力行程<br>Rated tonnage point            | 5 (mm)        |
| 滑块行程<br>Length of stroke                      | 150 (mm)     | 行程次数<br>Strokes per minute              | 32 (mm)       |
| 最大装模高度<br>Max. die height                     | 420 (mm)     | 装模高度调节量<br>Slide adjustment             | 100 (mm)      |
| 喉深<br>Depth of throat                         | 400 (mm)     | 工作台尺寸 (前后×左右)<br>Bolster area (FB×LR)   | 770×1400 (mm) |
| 滑块底面尺寸 (前后×左右)<br>Slide area (FB×LR)          | 450×600 (mm) | 模柄孔尺寸 (直径/深度)<br>Shank hole (Dia/Depth) | Φ60/90 (mm)   |
| 工作台板厚度<br>Bolster thickness                   | 160 (mm)     | 电机功率<br>Power of motor                  | 22 (kW)       |
| 外形尺寸 (左右)<br>Overall Dimensions (LR)          | 2295 (mm)    | 外形尺寸 (前后)<br>Overall Dimensions (FB)    | 2942 (mm)     |
| 外形尺寸 (高度)<br>Overall dimensions (H)           | 3670 (mm)    | 机器重量<br>Net Weight (about)              | 22000 (kg)    |
| 工作台面离地高度<br>Bolster surface height from floor | 970 (mm)     |                                         |               |