

|                                       |                                             |
|---------------------------------------|---------------------------------------------|
| 锭数<br>No. of spindles                 | 256                                         |
| 供丝筒子尺寸<br>Size of yarn winding bobbin | L240~320 x $\phi$ 42 x $\phi$ 110           |
| 卷取筒子尺寸<br>Size of winding bobbin      | $\phi$ 160x $\phi$ 89xL165xL173             |
| 锭距<br>Spindle gauge                   | 225mm                                       |
| 最高锭子转速<br>Max. Spindle speed          | 15000rpm                                    |
| 常用锭转速<br>Normal spindle speed         | 8000~14000rpm                               |
| 捻度范围<br>Twist range                   | 350~3989T/M                                 |
| 捻向<br>Twist direction                 | S or Z                                      |
| 锭子传动方式<br>Form of spindle driving     | 龙带循环传动<br>belt circulating drive            |
| 锭子固定<br>Spindle fixture               | 磁力固定<br>magnetic fixture                    |
| 起动方式<br>Start mode                    | Y- $\Delta$ 慢速起动<br>Star-delta slow start   |
| 张力器<br>Tensioner                      | 弹子张力器和垫圈式张力器并用<br>ball tension device       |
| 卷取长力<br>Take-up tension               | 调整丝线在超喂罗拉上的包围角<br>adjust the yarn in roller |
| 电机功率<br>Power of motor                | 7.5kw x 2                                   |
| 外形尺寸<br>Overall size                  | 16410 x 750 x 1895mm                        |